

2J Accessories and Parts

Grease Swivel Seals

page 2

Adjustable Equipment Legs

page 3

Floor Locks

page 4

Axles

page 5

Spanner Bushings

page 6

2J Accessories and Parts

Swivel Grease Seals

Swivel seals are designed to keep dirt and moisture out of the swivel raceway and lubricant in for easier swiveling and longer caster life. They are recommended for equipment exposed to frequent washings or sterilization cycles in hospitals, food processing plants and bakeries. To order as factory installed swivel caster option, add "GS" to end of caster model number.



2J Accessories and Parts

Adjustable Equipment Legs

With almost a century of providing to the food service industry, it only makes sense that Jarvis is able to utilize its global resources in advanced manufacturing technologies to develop additional solutions for our customers. Welded mounting plates available in two sizes

- Integral hex foot
- Available in multiple finishes
- Adjustments up to 1" in length
- Engineered solutions for custom applications
- Available in 4", 6" and 8" heights

Construction:

- 16 gauge steel tubing
- O.D. Tubing: 1-5/8" Hex Foot: 1-1/8"
- Load Capacity: 2000 lb static load



| Length (in) | Leg Model # | Overall Extended Height | Top Plate Dimensions | Bolt Hole Spacing | Mounting Bolt Size |
|-------------|-------------|-------------------------|----------------------|-------------------|--------------------|
| 4 | LEG4-22 | 5 | 2-3/8 x 3-5/8 | 1-3/4 x 3 | 5/16 |
| 4 | LEG4-72 | 5 | 3-1/2 x 3-1/2 | 2-5/8 x 2-5/8 | 9/32 |
| 6 | LEG6-22 | 7 | 2-3/8 x 3-5/8 | 1-3/4 x 3 | 5/16 |
| 6 | LEG6-72 | 7 | 3-1/2 x 3-1/2 | 2-5/8 x 2-5/8 | 9/32 |

2J Accessories and Parts

Floor Locks

Floor locks are designed to lock mobile equipment in a desired location. Often used on platform trucks, laundry carts and postal equipment, this unique locking system locks equipment in place with a simple press of the foot. Another press of the foot releases the lock for complete mobility. Floor locks are recommended for use on level surfaces only. Non-slip rubber brake pad on bottom of floor lock holds securely on a variety of floor surfaces.

These floor locks feature a 4" x 4-1/2" top plate with slotted mounting holes for 2-5/8" x 3-5/8" or 3" x 3". Mounting bolt size: 3/8".



| Wheel Diameter | Caster Series | Overall Extended Height | Retracted Height | Model Number |
|----------------|---------------|-------------------------|------------------|--------------|
| 4" | 61, 81 | 5-3/4" | 4-3/4" | FL4 |
| 5" | 61, 81 | 6-5/8" | 5-5/8" | FL5 |
| 6" | 61, 81 | 7-5/8" | 6-5/8" | FL6 |
| 8" | 61, 81 | 9-5/8" | 8-5/8" | FL8 |

2J Accessories and Parts

Axles

All Axles are Grade 2.

| Series | Description | Specifications | Part Number |
|-----------------------------------|-------------------|--------------------------------|-------------|
| 13 - 28 Series | Plain Axle | 5/16" diameter x 1-7/16" long | 902-02 |
| | Brake Axle | 5/16" diameter x 1-11/16" long | 957-02 |
| 30 - 40 Series / Swivels | Plain Axle | 3/8" diameter x 2-1/8" long | 927-02 |
| | Zerk Axle | 3/8" diameter x 2-1/8" long 9 | 28-12 |
| | Plain Brake Axle | 3/8" diameter x 2-1/4" long | 964-02 |
| | Zerk Brake Axle | 3/8" diameter x 2-1/4" long | 965-12 |
| 31 Series | Plain Axle | 3/8" diameter x 2-1/4" long | 932-22 |
| | Zerk Axle | 3/8" diameter x 2-1/4" long | 932-12 |
| 130 | Plain Axle | 3/8" diameter x 2-5/8" long | 966-02 |
| | Zerk Axle | 3/8" diameter x 2-5/8" long | 966-12 |
| | Plain Brake Axle | 3/8" diameter x 2-7/8" long | 961-02 |
| | Zerk Brake Axle | 3/8" diameter x 2-7/8" long | 961-12 |
| 130 | Plain Axle | 1/2" diameter x 2-3/4" long | 942-22 |
| | Zerk Axle | 1/2" diameter x 2-3/4" long | 942-12 |
| | Plain Brake Axle | 1/2" diameter x 3" long | 982-42 |
| | Zerk Brake Axle | 1/2" diameter x 3" long | 982-52 |
| 61-62 | Plain Axle | 1/2" diameter x 2-3/4" long | 942-22 |
| | Zerk Axle | 1/2" diameter x 2-3/4" long | 942-12 |
| | Plain Brake Axle | 1/2" diameter x 3" long | 982-42 |
| | Zerk Brake Axle | 1/2" diameter x 3" long | 982-52 |
| 81-82 | Series Plain Axle | 1/2" diameter x 3-3/8" long | 941-22 |
| 81SB | Zerk Axle | 1/2" diameter x 3-3/8" long | 941-12 |
| W81,W82, W87,W88, Pneumatic | Plain Axle | 1/2" diameter x 4" long | 980-22 |
| | Zerk Axle | 1/2" diameter x 4" long | 980-22 |
| | Zerk Axle | 3/8" diameter x 2.170 long | 928-37 |
| S30 - 40 | Brake Zerk Axle | 3/8" diameter x 2.22 long | 940-17 |
| S81 - 82 | Series Zerk Axle | 1/2" diameter x 3-3/8" long | 941-17 |

2J Accessories and Parts

Spanner Bushings

| Series | Specifications | Part Number |
|-------------------|---|-------------|
| 13 - 28 | 3/8" OD x 5/16" ID x 1.300" long | 4405-01 |
| S30 - S40 Series | 1/2" OD x 3/8" ID x 1.600" long | 4425-17 |
| (Stainless Steel) | 1/2" OD x 3/8" ID x 1.687" long | 4428-17 |
| W13-W28 Series | 1/2" OD x 3/8" ID x 1.600" long | 4425-17 |
| 30-40 Series | 1/2" OD x 3/8" ID x 1.575" long | 4426-12 |
| | 1/2" OD x 3/8" ID x 1.600" long | 4434-01 |
| | 1/2" OD x 3/8" ID x 1.610" long | 4425-02 |
| | 1/2" OD x 3/8" ID x 1.687" long | 4428-01 |
| | 9/16" OD x 3/8" ID x 2" long | 4478-01 |
| | 5/8" OD x 3/8" ID x 1.687" long | 4479-01 |
| 130-136 Series | 1/2" OD x 3/8" ID x 2" long | 4433-11 |
| | 5/8" OD x 3/8" ID x 2.031" long | 4487-01 |
| | 3/4" OD x 3/8" ID x 2" long | 4465-01 |
| 61- 62 Series | 9/16" OD x 3/8" ID x 2" long (3" wheel diameter only) | 4478-01 |
| | 3/4" OD x 3/8" ID x 2" long | 4465-01 |
| | 3/4" OD x 1/2" ID x 2.031" long | 4441-01 |
| | 3/4" OD x 1/2" ID x 2.120" long | 4423-01 |
| S81 - 82 Series | 3/4" OD x 1/2" ID x 2.260" long | 4494-17 |
| (Stainless Steel) | 3/4" OD x 1/2" ID x 2.437" long | 4498-17 |
| | 5/8" OD x 1/2" ID x 2.437" long | 4448-17 |
| 81 - 82 Series | 5/8" OD x 1/2" ID x 2.280" long | 4467-01 |
| | 5/8" OD x 1/2" ID x 2.437" long | 4431-01 |
| | 3/4" OD x 1/2" ID x 2.260" long | 4460-01 |
| | 3/4" OD x 1/2" ID x 2.437" long | 4458-01 |