

# 2J Swivel Locks

---

## **Swivel Lock (Welded)**

**Available on: 30 Series top plate casters  
(zinc, nickel plated & stainless steel)**

page 2

## **Swivel Lock (Welded)**

**Available on: 81 Series casters.**

page 2

## **Swivel Lock (Bolt-On)**

**Available on: 71, 81 and S81 Series casters**

page 3

# 2J Swivel Locks

---

## Swivel Lock (Welded)

**Available on: 30 Series top plate casters (zinc, nickel plated & stainless steel)**

1-Position swivel lock that is factory installed only. Hand operated plunger locks caster swivel in trailing position at 180° while wheel spins freely. Spring-loaded plunger mechanism is welded to top plate and features a clip that automatically locks in top of fork base when activated. To order as factory installed swivel caster option, add "1PSL" to end of caster model number.



## Swivel Lock (Welded)

**Available on: 81 Series casters.**

Designed for heavier loads and industrial applications, these 4-position swivel locks are welded to the bottom of the top plate and can convert swivel casters into rigid casters. The spring loaded plunger is hand operated and fits into notches cut in 90° intervals in the swivel raceway. Plunger locks out of way when not in use for free swiveling action. Factory installed only. To order as factory installed swivel lock, add "SL4" to end of caster model number.



# 2J Swivel Locks

---

## Swivel Lock (Bolt-On)

### Available on: 71, 81 and S81 Series casters

4-Position, bolt-on swivel lock is installed as the caster is mounted on the equipment. A springloaded, hand-operated plunger is engaged to fit into slots on the swivel raceway at 90° intervals while wheel spins freely. To disengage, simply pull out on the plunger pull ring and twist and lock so that it will not contact the swivel raceway. The caster fork base must be equipped with notches for this swivel lock to function. To order, specify swivel lock part number "3091-22". For stainless steel swivel lock order part number "3091-17".

