

4-71KHD SERIES — CONSTRUCTION FEATURES

Load Capacity Up to 2000 lbs.

- Single piece forged alloy steel top plate and fork base
- Precision raceways, CNC machined 2-1/8 in. diameter with 5/16 in. balls
- Induction hardened raceway ensure uniform depth of hardness
- Totally sealed swivel head
- 1/4 in. thick formed legs robotically welded inside and outside to 2-1/2 in. fork spacing
- 1/2 in. wheel axle
- Finish is bright zinc plated

RIG OPTIONS

- DL** 4-Way Directional Lock
TL/TE Total Lock / Trailing Edge
TL/LE Total Lock / Leading Edge
WFB Wheel Face Brake

TOP PLATE OPTIONS

71KHD (Standard)

Top Plate: 4" x 4-1/2"

Bolt Hole Centers: 2-5/8" x 3-5/8"

slotted to 3" x 3"

Attaching Bolt: 3/8"

72KHD (Optional)

Top Plate: 4-1/2" x 6-1/4"

Bolt Hole Centers: 2-7/16" x 4-15/16"

slotted to 3-5/8" x 5-1/4"

Attaching Bolt: 1/2"



Nylacron™ Wheels

With Precision Ball Bearings for Any Application


(NY/MD, NY/HSB, NY/MC, NY/GF)

Nylacron™ wheels with proper sized precision bearings are made to fit in any rig hub length and axle size. Nylacron™ wheels have greater load capacity ratings with better rollability while requiring less maintenance and have longer life.

**Total Lock
Leading Edge
(TL/LE)**



SWIVEL CROSS SECTION



TL/LE (Power Towing)



DL



The Swivel-EAZ™ (Dual-in-One) wheel easily turns a single wheel caster rig into a dual wheel premium urethane tread caster. Available in 4 Durometers: 70A (Black), 80A (Red), 95A (Blue) and 60D (Gray)

4-71KHD SERIES CASTER SPECIFICATIONS

Swivel Part Number	Rigid Part Number	Swivel Part Number with Rig Option (TL/LE)*	Dia. (in)	Width (in)	OAH (in)	Swl. Radius (in)	Cap. (lb)
NYLACRON™ MD (NY/MD) WHEELS WITH PRECISION BALL BEARINGS							
4-71KHD-NY/MD-P-0420-S	4-71KHD-NY/MD-P-0420-R	4-71KHD-NY/MD-P-0420-S-TL/LE	4	2	5-5/8	3-3/8	1600
4-71KHD-NY/MD-P-0520-S	4-71KHD-NY/MD-P-0520-R	4-71KHD-NY/MD-P-0520-S-TL/LE	5	2	6-1/2	4-1/4	2000
4-71KHD-NY/MD-P-0620-S	4-71KHD-NY/MD-P-0620-R	4-71KHD-NY/MD-P-0620-S-TL/LE	6	2	7-1/2	5	2000
4-71KHD-NY/MD-P-0820-S	4-71KHD-NY/MD-P-0820-R	4-71KHD-NY/MD-P-0820-S-TL/LE	8	2	9-1/2	6-1/8	2000
SOLID ELASTOMER (SE) WHEELS WITH PRECISION BALL BEARINGS							
4-71KHD-SE-P-0420-S	4-71KHD-SE-P-0420-R	4-71KHD-SE-P-0420-S-TL/LE	4	2	5-5/8	3-3/8	800
4-71KHD-SE-P-0520-S	4-71KHD-SE-P-0520-R	4-71KHD-SE-P-0520-S-TL/LE	5	2	6-1/2	4-1/4	1100
4-71KHD-SE-P-0620-S	4-71KHD-SE-P-0620-R	4-71KHD-SE-P-0620-S-TL/LE	6	2	7-1/2	5	1200
4-71KHD-SE-P-0820-S	4-71KHD-SE-P-0820-R	4-71KHD-SE-P-0820-S-TL/LE	8	2	9-1/2	6-1/8	1200
SWIVEL-EAZ™ (DUAL-IN-ONE) URETHANE 80A / FLAT TREAD (SWE/8/FT) WHEELS WITH PRECISION BALL BEARINGS (ALSO AVAILABLE IN CROWN TREAD)							
4-71KHD-SWE/8/FT-P-0420-S	4-71KHD-SWE/8/FT-P-0420-R	4-71KHD-SWE/8/FT-P-0420-S-FCB	4	2	5-5/8	3-3/8	700
4-71KHD-SWE/8/FT-P-0520-S	4-71KHD-SWE/8/FT-P-0520-R	4-71KHD-SWE/8/FT-P-0520-S-FCB	5	2	6-1/4	5-5/8	1050
4-71KHD-SWE/8/FT-P-0620-S	4-71KHD-SWE/8/FT-P-0620-R	4-71KHD-SWE/8/FT-P-0620-S-FCB	6	2	7-1/4	6-1/8	1400
4-71KHD-SWE/8/FT-P-0820-S	4-71KHD-SWE/8/FT-P-0820-R	4-71KHD-SWE/8/FT-P-0820-S-FCB	8	2	9-3/8	7-1/8	2000
SWIVEL-EAZ™ (DUAL-IN-ONE) URETHANE 95A / FLAT TREAD (SWE/9/FT) WHEELS WITH PRECISION BALL BEARINGS (ALSO AVAILABLE IN CROWN TREAD)							
4-71KHD-SWE/9/FT-P-0420-S	4-71KHD-SWE/9/FT-P-0420-R	4-71KHD-SWE/9/FT-P-0420-S-FCB	4	2	5-5/8	3-3/8	900
4-71KHD-SWE/9/FT-P-0520-S	4-71KHD-SWE/9/FT-P-0520-R	4-71KHD-SWE/9/FT-P-0520-S-FCB	5	2	6-1/4	5-5/8	1400
4-71KHD-SWE/9/FT-P-0620-S	4-71KHD-SWE/9/FT-P-0620-R	4-71KHD-SWE/9/FT-P-0620-S-FCB	6	2	7-1/4	6-1/8	1900
4-71KHD-SWE/9/FT-P-0820-S	4-71KHD-SWE/9/FT-P-0820-R	4-71KHD-SWE/9/FT-P-0820-S-FCB	8	2	9-3/8	7-1/8	2000

Nylacron™ (NY/MD, NY/HSB, NY/MC, NY/GL) wheels available in every size caster rig. Additional wheels available, consult Acorn™

*Add Rig Options to the end of each part number.

All sizes available with Vulkollan™ tread wheels and precision ball bearings.