

FEATURES

Load Capacity Up to 250 lbs.

- Double Ball Bearing Raceway
- Zinc Plated
- Yoke Thickness = 2mm
- Top Plate Thickness = 2.5mm

APPLICATIONS

- Vending machines
- Electronic & business machines
- Display stands & racks
- Meets high load cap. & low height requirements



1E-02 Series
Dual Wheel Caster



1E-03 Series
Single Wheel Caster

PLATES

Plate	Size	Bolt Pattern	Mounting Bolt Dia.
P1	2-3/8 x 3-5/8	1-3/4 x 2-7/8 to 3	5/16
P2	3-1/8 x 4-1/8	1-3/4 x 2-15/16 to 2-3/8 x 3/8	5/16
P3	4 x 4-1/2	2-5/8 x 3-5/8 to 3 x 3	3/8

STEMS

Stem	Size	Stem Type
TS41	1/2-13 x 1	Threaded Stem
TS43	1/2-13 x 1-1/2	Threaded Stem

CASTER SPECIFICATIONS

Wheel Dia. (in.)	Tread Width (in.)	Wheel Type	Capacity (lb)	OAH	Radius	Bearing	Swivel Part #	Rigid Part #
2	1-13/16	Polyolefin	250	2-7/8	1-7/8	Plain Bore	1E-02-P1*-PB-PL-0213-S-**	1E-02-PB-P1*PL-0213-R-**
2	1-13/16	Hard Rubber	250	2-7/8	1-7/8	Plain Bore	1E-02-P1*HR-PL-0213-S-**	1E-02-HR-P1*PL-0213-R-**

* Add PLATE size to part number.

** Add STEM size to part number.