

**FEATURES****Load Capacity Up to 200 lbs.**

- Double Ball Bearing Raceway
- Zinc Plated

**OPTIONS\*\*\***

- Side Lock Brake (SLB)

**STEMS\*\***

Stem	Size	Stem Type
TS43	1/2-13 x 1-1/2	Threaded Stem
PT58	3/4 NPT x 1	Pipe Thread
GR72	7/16 x 1-3/8	Grip Ring Stem
GR74	7/16 x 2	Grip Ring Stem

**PLATE AVAILABLE**

Plate	Size	Bolt Pattern	Mounting Bolt Dia.
P1	2-3/8 x 3-5/8	1-3/4 x 2-7/8 to 3	5/16

**CASTER SPECIFICATIONS**

Wheel Dia. (in.)	Tread Width (in.)	Wheel Type	Capacity (lb)	Capacity			Swivel Part #	Rigid Part #
				OAH	Radius	Bearing		
3	1	Hard Rubber	150	3-5/8	2-3/4	Plain Bore	1E-06-HR-PB-0310-S-**	1E-06-HR-PB-0310-R-**
3	1	Thermoplastic Rubber	130	3-5/8	2-3/4	Plain Bore	1E-06-TPR-PB-0310-S-**	1E-06-TPR-PB-0310-R-**
3	1	PU / Polyolefin	150	3-5/8	2-3/4	Plain Bore	1E-06-PB-PB-0310-S-**	1E-06-PB-PB-0310-R-**
3	1	Polyolefin	150	3-5/8	2-3/4	Plain Bore	1E-06-PP-PB-0310-S-**	1E-06-PP-PB-0310-R-**
4	1	Hard Rubber	175	4-5/8	3-3/8	Plain Bore	1E-06-HR-PB-0410-S-**	1E-06-HR-PB-0410-R-**
4	1	Thermoplastic Rubber	145	4-5/8	3-3/8	Plain Bore	1E-06-TPR-PB-0410-S-**	1E-06-TPR-PB-0410-R-**
4	1	PU / Polyolefin	175	4-5/8	3-3/8	Plain Bore	1E-06-PB-PB-0410-S-**	1E-06-PB-PB-0410-R-**
4	1	Polyolefin	175	4-5/8	3-3/8	Plain Bore	1E-06-PP-PB-0410-S-**	1E-06-PP-PB-0410-R-**
5	1	Hard Rubber	200	5-5/8	3-1/2	Plain Bore	1E-06-HR-PB-0510-S-**	1E-06-HR-PB-0510-R-**
5	1	Thermoplastic Rubber	150	5-5/8	3-1/2	Plain Bore	1E-06-TPR-PB-0510-S-**	1E-06-TPR-PB-0510-R-**
5	1	PU / Polyolefin	200	5-5/8	3-1/2	Plain Bore	1E-06-PB-PB-0510-S-**	1E-06-PB-PB-0510-R-**
5	1	Polyolefin	200	5-5/8	3-1/2	Plain Bore	1E-06-PP-PB-0510-S-**	1E-06-PP-PB-0510-R-**

\*\* Add STEM size to part number.

\*\*\* Add OPTION after the series.