

FEATURES

Load Capacity Up to 135 lbs.

- Dual Ball Raceway
- Luster Polished Chrome
- Precision Ball Bearing
- Neoprene Rubber 50-60 Durometer A

OPTIONS

- **SR:** Chrome Steel Dust Cover
- **HS:** Intergrated Posi-Lock Tread Brake

APPLICATIONS

- Laboratory Equipment
- IV Stands
- Mobile Computer Stands
- Medical Equipment
- Chairs



**Hollow Kingpin
Posi-Lock Brake Swivel (HS-23)**



**Hollow Kingpin
Swivel (23)**



**Hollow Kingpin Chrome Steel Dust
Cover with Total Lock Brake (HS-23-SR)**

**TOP PLATE**

00A: 1-1/4 x 2-3/8"

**HOLLOW KINGPIN**

23: 1-1/4 x 2-3/8"

**THREADED STEM**

33: 3/16" x 1-1/2"

**GRIP RING STEM**

70: 7/16" x 1"

70A: 7/16" x 7/8"

72: 7/16" x 1-3/8"

Wheel Dia.	Tread Width	Wheel Type	Load Cap.	OAH	Radius	Bearing	Swivel Part #
3	1	Neoprene Rubber	135	3-7/8	2-13-16	Flanged Ball	1E-NR-08CS310NPR41B-__*

* Add **00A** for Top Plate, **23** for Hollow Kingpin, **33** for Threaded Stem or **70 / 70A / 72** for Grip Ring Stem.

i.e. 1E-NR-08CS310NPR41B- **23** (Hollow Kingpin)

i.e. 1E-NR-08CS310NPR41B-**HS-23** (Hollow Kingpin with Posi-lock brake)