

## FEATURES

### Load Capacity Up to 220 lbs.

- Low profile, easy swiveling and smooth rolling.
- Durable zinc plated finish
- Non-marking TPR rubber tread
- Foot activated total lock brake
- Integrated thread guards
- Dual ball bearing raceway
- **Precision Ball Bearings in wheels for easier rollability**



## APPLICATIONS


- Patient Lifts
- Medical Equipment
- Computer Equipment

## HOLE SIZE

Specify: **H3**  
Hole Size: **12.8mm**  
Bolt Size: **1/2"**

## TOP PLATE

Specify: **TP01**



## CASTER SPECIFICATIONS

| Diameter (in.)                           | Tread Width (in.) | Wheel Description    | Capacity (lb) | Load Height in (mm) | Swivel Radius in (mm) | Wheel Bearing  | Part Number            |
|--|-------------------|----------------------|---------------|---------------------|-----------------------|----------------|------------------------|
| <b>TOP PLATE SWIVEL MODEL</b>            |                   |                      |               |                     |                       |                |                        |
| 3  | 2                 | Thermoplastic Rubber | 220           | 4-1/16" (103)       | 2-23/32 (69)          | Precision Ball | 1MC-DW-TPR-P-3-S-TP01  |
| <b>TOP PLATE SWIVEL TOTAL LOCK MODEL</b> |                   |                      |               |                     |                       |                |                        |
| 3  | 2                 | Thermoplastic Rubber | 220           | 4-1/16" (103)       | 3-1/2 (89)            | Precision Ball | 1MC-DW-TPR-P-3-TL-TP01 |
| <b>HOLLOW KINGPIN MODEL</b>              |                   |                      |               |                     |                       |                |                        |
| 3  | 2                 | Thermoplastic Rubber | 220           | 3-15/16" (100)      | 2-23/32 (69)          | Precision Ball | 1MC-DW-TPR-P-3-S-H3B   |
| <b>HOLLOW KINGPIN TOTAL LOCK MODEL</b>   |                   |                      |               |                     |                       |                |                        |
| 3  | 2                 | Thermoplastic Rubber | 220           | 3-15/16" (100)      | 3-1/2 (89)            | Precision Ball | 1MC-DW-TPR-P-3-TL-H3B  |



TOP PLATE SWIVEL MODEL



TOP PLATE SWIVEL  
TOTAL LOCK MODEL



HOLLOW KINGPIN MODEL



HOLLOW KINGPIN  
TOTAL LOCK MODEL