

CONSTRUCTION FEATURES

Load Capacity Up to 280 lbs.

- Lighter gauge steel economical caster series
- Double Ball Bearing Raceway
- Rivet Axle
- Zinc plated

PLATES

Plate	Size	Bolt Pattern	Bolt Dia.
01	2-3/8 x 3-5/8	1-3/4 x 2-7/8 to 3	5/16
02	3-1/8 x 4-1/8	1-3/4 x 2-15/16 to 2-3/8 x 3-3/8	5/16
03	4 x 4-1/2	2-5/8 x 3-5/8 to 3 x 3	3/8

STEMS

Stem	Size	Stem Type
40	1/2-13 x 3/4	Threaded Stem
43	1/2-13 x 1-1/2	Threaded Stem
72	7/16 x 1-3/8	Grip Ring Stem



Side Lock



Top Lock

2E-23 SERIES

Wheel Dia.	Tread Width	Wheel Type	Load Cap.	OAH	Radius	Bearing	Swivel Part #	Rigid Part #
3	1-1/4	Polyolefin	250	3-3/4	2-1/2	Plain Bore	2E-23CS314P090	2E-23CR314P090
3	1-1/4	Semi Steel	250	3-3/4	2-1/2	Plain Bore	2E-23CS314SS90	2E-23CR314SS90
3-1/2	1-1/4	Polyolefin	250	4-3/8	3	Plain Bore	2E-23CS3514P090	2E-23CR3514P090
3-1/2	1-1/4	Thermoplastic Rubber	250	4-3/8	3	Plain Bore	2E-23CS3514TPR90	2E-23CR3514TPR90
3-1/2	1-1/4	Duratough	250	4-3/8	3	Delrin	2E-23CS3514PTU55	2E-23CR3514PPU55
4	1-1/4	Polyolefin	275	4-5/8	3-1/4	Plain Bore	2E-23CS414P090	2E-23CR414P090
4	1-1/4	Thermoplastic Rubber	275	4-5/8	3-1/4	Plain Bore	2E-23CS414TPR90	2E-23CR414TPR90
4	1-1/4	Duratough	275	4-5/8	3-1/4	Delrin	2E-23CS414PTU55	2E-23CR414PPU55
5	1-1/4	Polyolefin	280	5-5/8	4-3/16	Plain Bore	2E-23CS514P090	2E-23CR514P090
5	1-1/4	Thermoplastic Rubber	280	5-5/8	4-3/16	Plain Bore	2E-23CS514TPR90	2E-23CR514TPR90
5	1-1/4	Duratough	280	5-5/8	4-3/16	Delrin	2E-23CS514PTU55	2E-23CR514PPU55

See Wheel Section for additional wheels to fit this series.