

CONSTRUCTION FEATURES

Load Capacity Up to 350 lbs.

- Glass-filled nylon construction for better strength
- Highly IMPACT absorbent
- Resists water
- Resists most chemicals, solvents, and oils.
- Smooth precision ball bearing raceway

APPLICATIONS

- Institutional, Medical, Electronic Equipment
- Carts

PLATES

Plate	Size	Bolt Pattern	Bolt Dia.
01	2-3/8 x 3-5/8	1-3/4 x 2-7/8 to 3	5/16



STEMS

Stem	Size	Stem Type
26	1/2	Hollow Kingpin
41	1/2-13 x 1	Threaded Stem
43	1/2-13 x 1-1/2	Threaded Stem
72	7/16 x 1-3/8	Grip Ring Stem



Directional Lock



Total Lock

2E-28 SERIES

Wheel Dia.	Tread Width	Wheel Type	Load Cap.	OAH	Radius	Bearing	Swivel (S) Part #	Rigid (R) Part #	Total Lock (TL) Part #	Directional Lock (DL) Part #
4	1-1/4	TPR*	230	5-7/16	3-3/8	Prec.	2E-28-TPR-P-0414-S	2E-28-TPR-P-0414-R	2E-28/TL-TPR-P-0414-S	2E-28/DL-TPR-P-0414-S
4	1-1/4	PP*	300	5-7/16	3-3/8	Prec.	2E-28-PP-P-0414-S	2E-28-PP-P-0414-R	2E-28/TL-PP-P-0414-S	2E-28/DL-PP-P-0414-S
5	1-1/4	TPR*	270	6-1/2	4-1/2	Prec.	2E-28-TPR-P-0514-S	2E-28-TPR-P-0514-R	2E-28/TL-TPR-P-0514-S	2E-28/DL-TPR-P-0514-S
5	1-1/4	PP*	350	6-1/2	4-1/2	Prec.	2E-28-PP-P-0514-S	2E-28-PP-P-0514-R	2E-28/TL-PP-P-0514-S	2E-28/DL-PP-P-0514-S

*Available with donut tread (TPR/DT or PP/DT)

See Wheel Section for additional wheels to fit this series.