

PREMIUM URETHANE / SWIVEL-EAZ® - URD/SWE

Capacity Up to 5600 lbs.




Swivel-EAZ® Wheels with Urethane Tread

A one-of-a-kind split outer tread wheel, the Swivel-EAZ® is the ultimate solution for the many industries searching to satisfy all of the ergonomic requirements and standards within today's environment. The technological design greatly reduces turning and rolling resistance on swivel, rigid and fixed axle systems.

Features

- Independent Swivel Surfaces
- Reduces Rolling Resistance
- Minimizes Initial Start Forces
- Prolongs the Life of the Swivel Caster
- Eliminates the Need for Costly Dual-Wheel Casters
- Carries 2x the Load of Standard Size Wheels with Similar Tread Hardness
- Offered in 4 Different Tread Hardness and Compounds to Fit Your Needs
- Maintenance-Free for Longer Life
- Non-Marking, High-Performance Elastomer Treads

Patented SWE® Design



**URD-SWE-820-CRN Wheels
Kingpinless HD Caster Rig**

Wheel Part Number*	Dia. (in.)	Width (in.)	Capacity 70A (lbs)	Capacity 80A (lbs)	Capacity 95A (lbs)	Capacity 60D (lbs)
Flat Tread with Precision Ball Bearings — 1/2" Axle — 2-1/2" Hub Length						
URD/SWE-320-FT	3	2	N/A	560	720	800
URD/SWE-420-FT	4	2	500	700	900	1000
URD/SWE-520-FT	5	2	200	1050	1400	1550
URD/SWE-620-FT	6	2	900	1400	1900	2200
URD/SWE-820-FT	8	2	1400	2300	3000	3500
Crown Tread with Precision Ball Bearings — 1/2" Axle — 2-1/2" Hub Length						
URD/SWE-320-CRN	3	2	N/A	320	400	520
URD/SWE-420-CRN	4	2	300	400	500	800
URD/SWE-520-CRN	5	2	450	650	800	1050
URD/SWE-620-CRN	6	2	600	900	1100	1300
URD/SWE-820-CRN	8	2	1100	1800	2400	2700
Flat Tread with Precision Ball Bearings — 3/4" Axle — 3" Hub Length						
URD/SWE-625-FT	6	2-1/2	900	1400	1900	2200
URD/SWE-825-FT	8	2-1/2	1400	2300	3000	3500
Crown Tread with Precision Ball Bearings — 3/4" Axle — 3" Hub Length						
URD/SWE-625-CRN	6	2-1/2	600	900	1100	1300
URD/SWE-825-CRN	8	2-1/2	1000	1800	2400	2700
Flat Tread with Precision Ball Bearings — 3/4" Axle — 3-1/2" Hub Length						
URD/SWE-630-FT-3/4	6	3	900	1400	1900	2200
URD/SWE-830-FT-3/4	8	3	1400	2300	3000	3500
URD/SWE-1030-FT-3/4	10*	3	2200	3700	4800	5600
*10-inch wheel available with 3/4, 1 or 1-1/4 inch axle						
Crown Tread with Precision Ball Bearings — 3/4" Axle — 3-1/2" Hub Length						
URD/SWE-630-CRN-3/4	6	3	600	900	1100	1300
URD/SWE-830-CRN-3/4	8	3	1100	1800	2400	2700
URD/SWE-1030-CRN-3/4	10*	3	2200	3700	4800	5600
*10-inch wheel available with 3/4, 1 or 1-1/4 inch axle						
HD Triple Wheel with Precision Ball Bearings — 3/4" Axle — 3-1/2" Hub Length						
HD-SWE-830-FT/FT/FT	8	3	1800	3000	3900	4550
HD-SWE-830-FT/CT/FT	8	3	1750	3000	3850	4500

*When ordering, note durometer after the part number (ex: URD/SWE-320-FT-60D)

Load capacities are for tow loads of 5-8 mph

For manual loads at 1-3 mph, multiply ratings above by 1.20